

HMK® R50 Paint and Varnish Remover

Strong, fast acting stripper.

Removes heavy varnishes, wax, urethane coatings, paint, oil & grease.

FOR PROFESSIONAL USE ONLY!



HMK® R50 is a strong fast acting stripper-cleaner for removing layers of hardened wax, varnish and lacquers as well as dried-in oils, adhesive residue (inc. carpet adhesive), urethane paint and graffiti from all polished or unpolished natural and artificial stone, ceramic and porcelain surfaces.

Instructions: Protect adjacent surfaces and apply a coat of R50 undiluted onto the cool, dry surface using a paintbrush or other soft brush and leave for 5 to 10 minutes but do not allow to dry. Once the coating has softened sufficiently, remove it carefully using a spatula, putty-knife or suitable brush, taking care not to scratch the surface. Afterwards scrub the area vigorously with HMK® R55 Intensive Cleaner -acid free-diluted about 1:10 with clean water, using a scrubbing brush, stiff brush or suitable pad. Remove the dirty liquid and rinse the area thoroughly with clean water. For very old hardened layers repeat the treatment as necessary.

When using a wet vacuum we recommend that you add HMK® Z102 Defoamer to the water to regulate the amount of foam.

Important: Do not apply in direct sunlight. Do not apply on rubber, plastic, perspex, polished-lacquered or waxed wood and solvent intolerant surfaces. If these areas are splashed, remove splashes immediately and rinse thoroughly with clean water. Remove all foodstuffs from the area to be treated before work is commenced.

Coverage: About 2-4m²/litre.

Danger: Chemical product. Contains dichloromethane. Toxic and Combustible. Keep away from heat and flame. Harmful or fatal if swallowed or inhaled. Ensure adequate ventilation during application and wear protective clothing. Avoid eye/skin contact and breathing vapour or mist. If exposed flush/wash with water and seek medical attention. Keep container closed and out of the reach of children. See Material Safety Data Sheet for more detailed information.

Packaging: 12 x 1 litre bottles/box.

Storage: Store in cool place.

Testing: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12 and above 25°C.

Limitation of liability: The liability of HMK® Moeller Stonecare for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stonecare shall not be liable for any consequential damages. No other warranty or representation is made or implied.